

TECHNICAL DATASHEET - TOPSHIELD

DESCRIPTION

Topshield is a highly concentrated, environmentally friendly accelerator for HyDra Rubber LM. Topshield is applied on top of the HyDra Rubber LM product, which accelerates the curing time of the HyDra Rubber LM product. Topshield immediately removes a large part of the moisture percentage of HyDra Rubber LM causing an immediate "skin formation" on the HyDra Rubber LM product. This causes the products to dry faster and more resistant to, for example rainfall.

Topshield is an environmentally friendly product and can be used indoors and outdoors without special protection.

APPLICATION

Topshield is available in 1L bottles with spray trigger. Spray Topshield lightly over the HyDra Rubber LM product with an average distance of +/- 20 cm from the surface. The top layer of the product will be dry to touch immediately.

RESTRICTIONS

Obey the safety precautions when applying by wearing gloves, eye protection and other suitable protective equipment. Please refer to the SDS sheet for more information.

If there are multiple layers of HyDra Rubber LM applied, only use Topshield on the last layer of HyDra Rubber LM. *If Topshield is applied in between two layers of HyDra Rubber LM, it could harm the adhesion of the layers.*

TECHNICAL DATA

PROPERTIES	TYPICAL RESULTS
Color	Transparent
Physical properties	Liquid
Specific gravity (liquid), g/cm ³	CA. 1.0
Odor	None

WARNING

Topshield should not be applied when the ambient temperature is lower than 0°C. During extreme rainfall is not recommended to use Topshield. For professional use only. Keep out of reach of children. Do not store product in direct sunlight, maximum 32°C (90°F) and minimum 5°C (41°F).



HyDra Rubber LM

We reserve the right for printing errors and refer to the fact that the current version of the data is always available at www.hydratec.se or can be requested by contacting our office. Current revision number is in the top left corner.