

## TECHNICAL DATASHEET - WINTERGRADE

### DESCRIPTION

WinterGrade is an anti-freeze additive for the use of HyDra Rubber LM up to temperatures as low as -10°C (surface- and air temperature).

### APPLICATION

WinterGrade are available in containers of 200ml. One container WinterGrade is mixed with one pail of HyDra Rubber LM 20KG.

### RESTRICTIONS

Obey the safety precautions when applying by wearing gloves, eye protection and other suitable protective equipment. Please refer to the SDS sheet for more information. Use WinterGrade only when the ambient temperature is below 0°C during installation, or below 0°C during the curing phase of the product. The drying time of HyDra Rubber LM will be extended when using Wintergrade.

### STORAGE

Keep container tightly closed. Keep container in cool, well ventilated area, away from heat and sources of ignition.

### TECHNICAL DATA

PROPERTIES	TYPICAL RESULTS
Color	Yellow- Brown
Physical properties	Liquid
Specific gravity (liquid), g/cm3	CA. 1.0
Odor	None



### WARNING

In case of contact with eyes, immediately flush with water. May cause skin irritation. Do not ingest. Do not breathe gas/fumes/vapor/spray. In case of leaks absorb with inert material. Sweep or scoop up and put in disposable container. Flush area with plenty of water.



HyDra Rubber LM